



570-600Wp

N-TOPCon

Bifacial Monocrystalline Module

2279x1134x30

.....
Dimensions (mm)

144 CELL

.....
Mono TOPCon

570-600Wp

.....
Power output

1500 VDC

.....
Max. system voltage

22.83%

.....
Max. efficiency

KEY FEATURES



Higher Power Output

Module power increases by 5-25% generally, bringing significantly lower LCOE and higher IRR. 0-5w positive tolerance output warranty.



Optimal Choice for Ultra-large Power Plants

Contribute to Lower BOS cost and LCOE.



ZERO LID

N-Type cell is characterized by "0" LID, which generates more power.



PID Resistance

Excellent Anti-PID performance guarantee via optimized mass-production process and material control.



Durability Against Extreme Environmental Conditions

High salt mist and ammonia resistance certified by TUV NORD. Lower temperature coefficient and operating temperature.



More Outstanding Low-light Performance

Higher power output even under low-light environments like on cloudy days



Enhanced Mechanical Load

Certified to withstand: wind load (2400 Pa) and snow load (5400 Pa).



EL Full Inspection

100% EL Inspection.

Comprehensive Products and System Certificates

IEC61215/IEC61730/IEC61701/IS14286/IEC61853-1/IEC62804-1

ISO 9001: Quality Management System

ISO 14001: Environmental Management System

ISO 27001: Information Security Management System


GMP-Good Manufacturing Practices

ISO 14064: Greenhouse Gases Emissions Verification


OHSAS 18001: Occupational Health and Safety Management System

LINEAR PERFORMANCE WARRANTY


12-year product warranty / 30-year linear power warrant




Dimensions of PV Module



SUN144TXXX(XXX=Wp) (570Wp-600Wp) I-V characteristics at different irradiances



I-V characteristics at different temperatures



ELECTRICAL CHARACTERISTICS (STC*)

Rated Power in Watts-Pmax(Wp)	SUN144T570	SUN144T575	SUN144T580	SUN144T585	SUN144T590	SUN144T600
Open Circuit Voltage-Voc(V)	51.07	51.27	51.47	51.67	51.87	52.27
Short Circuit Current-Isc(A)	14.25	14.31	14.37	14.43	14.49	14.61
Max. Power Voltage-Vmpp(V)	42.29	42.44	42.59	42.74	42.89	43.19
Max. Power Current-Impp(A)	13.48	13.55	13.62	13.69	13.76	13.90
Module Efficiency(%)	22.06	22.25	22.44	22.64	22.83	23.26
Maximum system voltage	1500 vdc					
Fuse Rating(A)	30					
Temperature coefficient Pmax	-0.3561%/ C					
Temperature coefficient Isc	0.0547%/ C					
Temperature coefficient Voc	-0.2853%/ C					
Refer. Bifacial Factor	80±5%					

*STC: Irradiance 1000W/m², module temperature 25°C, AM=1.5

WORKING CHARACTERISTICS (NOCT*)

Rated Power in Watts-Pmax(Wp)	428	431	435	439	443	452
Open Circuit Voltage-Voc(V)	48.52	48.71	48.90	49.09	49.28	49.65
Short Circuit Current-Isc(A)	11.40	11.45	11.50	11.54	11.59	11.80
Max. Power Voltage-Vmpp(V)	39.33	39.47	39.61	39.75	39.89	40.30
Max. Power Current-Impp(A)	10.78	10.84	10.90	10.95	11.01	11.18
Power tolerance	0~+3%					
NOCT	45°C±2°C					
Operating Temperature	-40°C~85°C					

*NOCT: Irradiance 800W/m², ambient temperature 20°C, wind speed 1m/s

Electrical characteristics with different rear side power gain

5%	Pmax(Wp)	599	604	609	614	620	632
	Efficiency(%)	22.75	22.55	22.35	22.14	21.94	24.37
15%	Pmax(Wp)	656	661	667	673	679	691
	Efficiency(%)	24.92	24.70	24.47	24.25	24.03	24.37
25%	Pmax(Wp)	713	719	725	731	738	752
	Efficiency(%)	27.09	26.84	26.60	26.36	26.12	29.02

The additional gain from the rear side compared to the power of the front side at the standard test condition. It depends on mounting (structure, height, tilt angle etc.) and albedo of the ground.

MECHANICAL CHARACTERISTICS

Number of cells	144pcs	Type of frame	Anodized Aluminum Alloy
Size of cell(mm)	182.2 X 91/91.8	Size of module(mm)	2279×1134×30
Type of cell	N-TOPCon Mono	Weight(kg)	33
Thickness of glass(mm)	2.0	Cables/connectors	4.0mm², MC4 compatible
Junction box	IP68	Length of Cabel	+300mm/-300mm(connector included)

PACKAGING CONFIGURATION

Height of Modules (mm)	35	30
Number of Modules Per Pallet	31	36
Packaging Box Dimensions (l×w×h) (mm)	2300×1120×1260	2300×1120×1260
Box Gross Weight (kg)	1084	1210
Number of Modules Per 40ft (HQ) Container	620	720
Number of Pallets Per 40ft (HQ) Container	20	20

Caution: Please read safety and installation instructions before using the product

*Warranty: As per Product warranty. Disclaimer: V-Guard Solar reserves the right to make any adjustment to the information described here. Dataset contained in this specification do not from a representative of a single module data. @T&C Apply.

Contact us: Sales Queries: 0484-2005000, 4335000 | Email: customercare@vguard.in
V-Guard Care: 0120-4850100 | 1860 180 3000

The Specification and key features contained in this datasheet may deviate slightly from our actual products due to the on-going innovation & product enhancement, V-Guard Industries Limited reserves the right to make necessary adjustment to the information described herein at any time without further notice.